

Declaration om Performance

Article-ID:

RY 100 1,0, RY 100 1,2, RY 145 1,2, RY 195 1,0, RY 195 1,2, RY 195 1,5, RY 195 2,0, SKY 100 1,0, SKY 100 1,2, SKY 195 1,2, SKY 195 2,0, SKYEP 145 1,2, SKYEP 195 1,2, VFL 70 AZ 0,7, VFL 70 PL 0,7

Intended use:

Internally to support gypsum plasterboard systems

Manufacturer:

*Europrofil AB
Box 147
S - 71323 Nora
Sweden*

Verification of constancy: System 4

Art_ID	QUALITY	PROFILE	DIMENSION	REACTION TO FIRE	FLEXURAL TENSILE STRENGTH	EN_ID
RY 100 1,0	Z 275	C	48/100/52/1,0	Class A1	350 N/mm ²	14195
RY 100 1,2	Z 275	C	48/100/52/1,2	Class A1	350 N/mm ²	14195
RY 145 1,2	Z 275	C	48/145/52/1,2	Class A1	350 N/mm ²	14195
RY 195 1,0	Z 275	C	48/195/52/1,0	Class A1	350 N/mm ²	14195
RY 195 1,2	Z 275	C	48/195/52/1,2	Class A1	350 N/mm ²	14195
RY 195 1,5	Z 275	C	48/195/54/1,5	Class A1	350 N/mm ²	14195
RY 195 2,0	Z 275	C	48/195/54/2,0	Class A1	350 N/mm ²	14195
SKY 100 1,0	Z 275	U	57,00/100/57,00/1,0	Class A1	350 N/mm ²	14195
SKY 100 1,2	Z 275	U	57,20/100/57,20/1,2	Class A1	350 N/mm ²	14195
SKY 195 1,2	Z 275	U	57,20/195/57,20/1,2	Class A1	350 N/mm ²	14195
SKY 195 2,0	Z 275	U	58,00/195/58,00/2,0	Class A1	350 N/mm ²	14195
SKYEP 145 1,2	Z 275	U	57,20/145/57,20/1,2	Class F	350 N/mm ²	14195
SKYEP 195 1,2	Z 275	U	57,20/195/57,20/1,2	Class F	350 N/mm ²	14195
VFL 70 AZ 0,7	AZ 185	W	25/70/25/0,7	Class A1	220 N/mm ²	14195
VFL 70 PL 0,7	Z 275+2*25 µm polyester coating	W	25/70/25/0,7	Class A1	220 N/mm ²	14195

The performance of the product identified above is in conformity with the declared performance identified in the table. Signed for and on behalf of Europrofil AB by:

Christian Carlsson, CEO

Nora, Sweden - 2013-04-26



Christian Carlsson, CEO