



DECLARATION OF PERFORMANCE

No 0010_Knauf_Beto_M_Plus_2019-02-14

1. Unique identification code of the product-type: **0,3 Mpa - A2-s1, d0 – Knauf Beto M Plus**
2. Intended use/es: **On internal walls, ceilings, columns and partitions**
3. Manufacturer: **Knauf Gips KG | Am Bahnhof 7 | D-97346 Iphofen
Tel: +49 (9323) 31-0
Fax: +49 (9323) 31-277
e-mail: zentrale@knauf.de**
4. Authorised representative: **not relevant**
5. System/s of AVCP: **System 4**
6. a) Harmonised standard: **EN 15824:2017**
Notified body/ies:
6. b) European Assessment Document: **not relevant**
European Technical Assessment: **not relevant**
Technical Assessment Body: **not relevant**
Notified body/ies: **not relevant**
7. Declared performance/s:

Essential characteristics		Performance
Adhesion		≥ 0,3 Mpa
Thermal conductivity	λ	NPD
Reaction to fire	R2F	A2-s1, d0
Dangerous substances	DS	NPD
8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Iphofen, 2019-02-14

i. V. Dr. Wolfgang Rümmler
(Head of Research & Development D/CH | Knauf Gips KG)

i. V. Dr. Norbert Wings
(Head of Product Development | Competence Centre Readymix Compounds | Knauf Gips KG)